



Simplified Moisture Management, Easy Installation, and Superior Performance.

FEATURES/BENEFITS

Description

Easy-Fur™ is a rollable nylon furring strip that creates uniform separation between cladding and sheathing to allow air and moisture to circulate freely, which reduces the risk of water damage while enhancing thermal performance. Its durable, nylon construction withstands environmental stresses, maintaining its shape and function over time.

Designed to replace wood furring strips, **Easy-Fur™** simplifies and reduces installation time while ensuring a consistent cavity space for drainage and ventilation behind multiple types of cladding.

Benefits

- **Moisture Management:** Mesh design creates a consistent, omni-directional 10 mm gap for moisture to drain and air to circulate, increasing the life of the siding.
- **Reduced Installation Time:** Faster to install than traditional furring strips, as it can be rolled onto the wall and cut to length.
- **Enhanced Breathability:** Allows moisture vapor to escape, reducing the risk of mold & mildew.
- **Durability:** Structured Strand™ extruded polymer material is resistant to most known corrosive chemicals, including solvents, and will not split, warp, or rot.
- **Easy Installation:** Lightweight material; Can be cut with scissors, attached with a hammer tacker, and siding can be nailed directly through the mesh.
- **Fire-Resistant:** Easy-Fur™ passes multiple wall assemblies that require NFPA 285

Applications

- Wood Siding
- Metal Siding
- Fiber Cement Board Siding
- Other Wall / Roof Applications

A Better Solution Than Wood or Metal

Builders no longer need to rely on outdated materials like wood or metal for furring now that Easy-Fur™ offers a better solution. Unlike traditional wood, which can absorb moisture, warp, rot, and attract insects, Easy-Fur™ is lightweight, durable, and easy to install. It promotes air and moisture movement behind cladding, delivering superior long-term performance with less hassle—making it the smarter, healthier choice for modern construction.



Product Comparison

Description	Easy-Fur™	Wood Furring	Metal Furring
Resists warping	✓	✗	✓
Resists mold, mildew, and rot	✓	✗	✓
Improved labor efficiency	✓	✗	✗
Minimizes penetrations	✓	✗	✗
Dimensionally stable	✓	✗	✓
Omni-directional ventilation	✓	✗	✗
Size	25 ft	8 ft	10 ft

Physical Properties

Description	Measurement	Test Method
Material	Recycled Nylon	
Thickness	0.40 in / 10.2 mm	
Roll Length	25 ft / 7.6 m	
Roll Width	4 in / 10.2 cm	
Roll Coverage	8.3 sq ft	
Roll Weight	1.5 lbs	
Rolls per Bundle	4	
Bundles per Pallet	45	
Rolls per Pallet	180	

Important Notice

Review all local and state building codes for specific fastening and installation requirements. Always follow all OSHA safety rules and use great attentiveness to prevent damage to Easy-Fur™ during installation process. Any damaged Easy-Fur™ should be repaired before installation of roofing and/or siding material.

*Aging in Accordance to ASTM E2556 A.1.2

LIMITED WARRANTY: Keene Building Products, Inc. ("Keene") warrants its Driwall products against defects in material and workmanship for a period of Twenty-Five (25) years from the date of installation. Upon receipt of written notice, which must be given no later than thirty (30) days after discovery of the defect, Keene, at its sole option, will repair or replace the defective item(s) or refund the purchase price. Keene, at its sole option, may request that the defective item(s) be returned to Keene's principal offices for investigation and inspection. Keene is not required to repair or replace the defective item(s) or to refund the purchase price until it has received such item(s) that Keene has requested returned and has inspected such item(s).

The warranty provided above is extended solely to the person or entity that purchases the product directly from Keene, and no third party may rely thereon or assert any claim based on such warranty. The foregoing warranty is the only warranty provided by Keene and is to the exclusion of any other warranty, whether express or implied, including the implied warranties of merchantability and fitness for a particular purpose, all of which are expressly disclaimed. Keene's liability, if any, for damages based on any claim of any kind whatsoever, and regardless of the legal theory, with regard to any of its products shall be limited to the actual purchase price of the product(s) with respect to which such claim is made.

UNDER NO CIRCUMSTANCES SHALL KEENE BE LIABLE TO PURCHASER FOR COMPENSATION, REIMBURSEMENT OR DAMAGES ON ACCOUNT OF THE LOSS OF PRESENT OR PROSPECTIVE PROFITS OR REVENUE, EXPENDITURES, INVESTMENTS OR COMMITMENTS, AND IN NO EVENT SHALL KEENE BE LIABLE TO PURCHASER OR ANY OTHER PERSON OR ENTITY FOR SPECIAL, INCIDENTAL, INDIRECT, CONSEQUENTIAL OR EXEMPLARY DAMAGES. By way of example only, Keene will not be responsible for any damages purchaser may incur that are related to surface, subsurface or building conditions, damage to the structure or contents of any building, or for costs of repair and replacement except as may be expressly provided in this Limited Warranty (and subject to the terms and conditions hereof).

Keene shall not be liable for product failure resulting from any of the following: (i) products not installed in accordance with Keene's installation instructions; (ii) non-compliance with applicable building codes and regulations; (iii) the use of any of its products (A) in a manner for which it was not intended; (B) in a modified form without the permission of Keene, or (C) in combination with any other system, equipment or device not manufactured or sold by Keene.

Keene may change, modify, amend, replace or discontinue offering a product warranty, limited or otherwise. Any such change, modification, amendment, replacement or discontinuance shall be applicable to unsold products only, and Keene shall endeavor to give purchaser at least thirty (30) days prior written notice of same.

Claims or inquiries shall be addressed as follows:
Customer Service Department [Quality Control Manager]

KEENE BUILDING PRODUCTS, INC.
2926 Chester Ave.
Cleveland, OH 44114
P 440 605 1020 [877-514-5336]
F 440 605 1120

